Eaton 2063PMURF

Catalog Number: 2063PMURF

Eaton LV Unipak capacitor bank, UNIPAK, Low Voltage Fixed Capacitor Banks, 19.6A, 600V, Three-phase, 20 kVAR, Protected, Neon red blown-fuse indicating lights, Three slottedblade-type fuses, A2 Frame

General specifications



Eaton LV Unipak capacitor bank

UPC

782116059119

Product Height

22.3 in

Product Weight

30.63 lb

Catalog Number

2063PMURF

Product Length/Depth

5.954 in

Product Width

8.5 in

Warranty

Eaton Selling Policy 25-000, one (1) year

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

whichever occurs first.

Certifications Catalog Notes

CSA Certified Multiply the 240V kVAR rating by 0.75 to UL Listed calculate the kVAR value at 208V.





defaultTaxonomyAttributeLabel

Type

UNIPAK

Amperage Rating

19.60A

Fuse type

Three slottedblade type fuses with 200,000 ampere interrupting capacity, Fuses mounted on stand-off bushings or fuse blocks, solderless connectors for easy hookup of incoming line conductors.

Phase

Three-phase

Product Category

Low Voltage Fixed Capacitor Banks

Voltage rating

600 V

Enclosure

NEMA 1, NEMA 3R

Enclosure material

14 gauge steel finished with durable powder coat finish

Frame size

A2

Indicators

Red, neon blown-fuse indicating lights are protected by transparent weatherproof guard

Protection

Three fuses, three lights

Rating

20 kVAR

Resources

Catalogs

Eaton's Volume 3—Power Distribution and Control Assemblies

Specifications and datasheets

Eaton Specification Sheet - 2063 PMURF



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia