

Eaton 1150E-6513

Catalog Number: 1150E-6513

Eaton Enhanced 50 Series Photoelectric Sensor, Photoelectric, Right Angle, Sensor distance: 200 Ft., 6.6 Ft. (2m) Cable, 12–240 Vdc 24–240 Vac input, Reverse polarity, short circuit and overload, Thu-Beam, 6.6 Ft. (2m)

General specifications



Product Name	Catalog Number
Eaton Enhanced 50 photoelectric sensor	1150E-6513
UPC	Product Length/Depth
782116112562	1.91 in
Product Height	Product Width
3.46 in	1.81 in
Product Weight	Warranty
0.5375 lb	3 year
Compliances	Certifications
Contact Manufacturer CE Marked	CSA Certified

defaultTaxonomyAttributeLabel

Cable type

Polyvinyl Chloride (PVC)

Enclosure material

Fiberglass reinforced plastic

Operating mode

Thru-beam

Connection

6.6 ft (2 m) cable

Sensor type

Through beam

Switch type

Photoelectric

Input voltage

12-240 Vdc, 24-240 Vac

LED indicator

Power on: yellow

Protection

Reverse polarity and short circuit protected

Cord length

79.2 ft

Operating temperature - max

131 °F

Operating temperature - min

-13 °F

Environmental rating

IP67, IP69K

Resources

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - 1150E-6513](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)