

Eaton 1351E-6504

Catalog Number: 1351E-6504

Eaton Enhanced 50 Series Photoelectric Sensor, Photoelectric, Right Angle, Sensor distance: 10 Ft., 3A max AC, SPDT Form C Relay, 3A at 240 Vac, 5 Pin Mini Connector, 12–240 Vdc 24–240 Vac input, Diffuse Reflective



General specifications

Product Name	Catalog Number
Eaton Enhanced 50 photoelectric sensor	1351E-6504
UPC	Product Length/Depth
782116111770	1.91 in
Product Height	Product Width
4.16 in	1.81 in
Product Weight	Warranty
0.3375 lb	3 year
Compliances	Certifications
Contact Manufacturer RoHS Compliant	CSA Certified

defaultTaxonomyAttributeLabel

Contact Rating

3A at 240 Vac

Enclosure material

Fiberglass reinforced plastic

Operating mode

Diffuse reflective

Connection

5-pin mini connector

Contact configuration

SPDT form C relay

Sensor type

Diffuse reflective

Switch type

Photoelectric

Input voltage

12-240 Vdc, 24-240 Vac

LED indicator

Output status: green

Marginal gain: red

Power on: yellow

Maximum AC current

3 A

Operating temperature - max

131 °F

Operating temperature - min

-13 °F

Environmental rating

IP67, IP69K

Resources

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - 1351E-6504](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)