

# Eaton C25DRF340A

Catalog Number: C25DRF340A

Eaton definite purpose contactor, Non-reversing contactors and starters ,Open with DIN rail mounting adapter ,Box lugs (posidrive setscrew) and quick connect terminals (side-by-side) ,110–120 Vac, 50/60 Hz,3P ,40A

## General specifications



<b>Product Name</b>	<b>Catalog Number</b>
Eaton definite purpose contactor	C25DRF340A
<b>UPC</b>	<b>Product Length/Depth</b>
782116483952	3.35 in
<b>Product Height</b>	<b>Product Width</b>
3.75 in	2.4 in
<b>Product Weight</b>	<b>Warranty</b>
1.19 lb	1 year
<b>Compliances</b>	<b>Certifications</b>
RoHS Compliant	CSA Certified
	UL Recognized
	UL Listed file E1491 (Guide Number NLDX2)

## defaultTaxonomyAttributeLabel

### Amperage Rating

40A

### Number Of Poles

Three-pole

### Options

Global listed

### Type

Non-reversing

### Auxiliary contacts

Quick connect (side-by-side)

### Coil

110-120 Vac, 50/60 Hz

### Coil voltage

208-240 Vac, 50-60 Hz

### Enclosure

Open with DIN rail mounting adapter

### Frame size

15-50 A, two-pole and three-pole

### Inductive full load

40 A

### Model

Contactor

### Resistive load

50 A

### Series

D1

### Terminals

Box lugs (posidrive setscrew) and quick connect terminals (side-by-side)

### Connection

Quick

## Resources

### Catalogs

Eaton's Volume 5—Motor Control and Protection

### Drawings

C25DRF3 AutoCAD 2D Footprint (mm)

C25DRF3 3D Inventor

C25DRF3 3D Model Xchange

C25DRF3 2D PDF

C25DRF3 AutoCAD 2D Footprint

C25DRF3 2D Drawing Xchange

### Specifications and datasheets

Eaton Specification Sheet - C25DRF340A



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)