

Eaton C25GNF390T

Catalog Number: C25GNF390T

Eaton definite purpose contactor, 90A, two- and three-pole ,Open with metal mounting plate,24 Vac, 50/60 Hz



General specifications

Product Name	Catalog Number
Eaton definite purpose contactor	C25GNF390T
UPC	Product Length/Depth
782114100196	3.97 in
Product Height	Product Width
3.75 in	2.63 in
Product Weight	Warranty
3 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Compliances	Certifications
RoHS Compliant	CSA Certified
CE Marked	UL Listed file E1491 (Guide Number NLDX2)
	UL Recognized

defaultTaxonomyAttributeLabel

Accessories

Mounting plate

Amperage Rating

120A

Number Of Poles

Three-pole

Options

Individual pkg.

Type

Non-reversing

Auxiliary contacts

Quick connect (side-by-side)

Coil

24 Vac, 50/60 Hz

Coil voltage

24 Vac, 50/60 Hz

Contact configuration

1 NO, 1 NC

Enclosure

Open with metal mounting plate

Frame size

15-50 A, two-pole and three-pole

Inductive full load

120 A

Model

Contactors

Resistive load

140 A

Series

F1

Terminals

Box lugs (posidrive setscrew)

Connection

Quick

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

C25GNF3 AutoCAD 2D Footprint (mm)

C25GNF3 3D Inventor

C25GNF3 AutoCAD 2D Footprint

C25GNF3 2D Drawing Xchange

C25GNF3 2D PDF

C25GNF3 3D Model Xchange

Specifications and datasheets

Eaton Specification Sheet - C25GNF390T



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)