Eaton C25FNE360A

Catalog Number: C25FNE360A

Eaton definite purpose contactor, Quick, 75A, 110-120 Vac, 50/60 Hz, 1NO, Open with metal mounting plate, 15-50A, two- and 3P, 75A, Contactor, 3P, 90A, Box lugs (posidrive setscrew) and quick connect terminals, Non-reversing

General specifications

Eaton definite purpose contactor



UPC

782113549422 Product Height

Product Name

3.75 in

Product Weight

2.66 lb

Compliances

RoHS Compliant

Catalog Notes

Resitive Load rating per pole

Catalog Number

C25FNE360A

Product Length/Depth

3.97 in

Product Width

2.63 in

Warranty

1 year

Certifications

UL Recognized

CSA Certified



defaultTaxonomyAttributeLabel

Amperage Rating

50A

Number Of Poles

Two-pole

Type

Non-reversing

Coil

110-120 Vac, 50/60 Hz

Enclosure

Open with metal mounting plate

Frame size

15-50 A, two-pole and three-pole

Inductive full load

50 A

Model

Contactor

Resistive load

65 A

Terminals

Box lugs (posidrive setscrew) and quick connect terminals (side-

by-side)

Connection

Quick

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Specifications and datasheets

Eaton Specification Sheet - C25FNE360A



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia