Eaton C25END440B

Catalog Number: C25END440B

Eaton definite purpose contactor, Quick, 60A, 110-120 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 60A, Contactor, Two-pole, 75A, Box lugs (posidrive setscrew) and quick connect terminals, Non-reversing

General specifications



Product Name

Eaton definite purpose contactor

UPC

782113620770

Product Height

3.75 in

Product Weight

2.1 lb

Compliances

RoHS Compliant

Catalog Notes

Resitive Load rating per pole

Catalog Number

C25END440B

Product Length/Depth

3.38 in

Product Width

2.68 in

Warranty

1 year

Certifications

CSA Certified

UL Recognized



defaultTaxonomyAttributeLabel

Amperage Rating

40A

Number Of Poles

Four-pole

Type

Non-reversing

Coil

110-120 Vac, 50/60 Hz

Enclosure

Open with metal mounting plate

Frame size

15-50 A, two-pole and three-pole

Inductive full load

40 A

Model

Contactor

Resistive load

50 A

Terminals

Box lugs (posidrive setscrew)

Connection

Quick

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Specifications and datasheets

Eaton Specification Sheet - C25END440B



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia