

# Eaton C25LNE3360A

Catalog Number: C25LNE3360A

Eaton definite purpose contactor, Non-reversing contactors and starters (C306), 360A, three-pole, Open with metal mounting plate, Box lugs (posidrive setscrew) ,Three Pole, 360A,110–120 Vac, 50/60 Hz



Photo is representative

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton definite purpose contactor	C25LNE3360A
<b>UPC</b>	<b>Product Length/Depth</b>
782114181584	7.78 in
<b>Product Height</b>	<b>Product Width</b>
13.12 in	7.05 in
<b>Product Weight</b>	<b>Warranty</b>
27.7 lb	1 year
<b>Compliances</b>	<b>Certifications</b>
RoHS Compliant	UL Recognized CSA Certified
<b>Catalog Notes</b>	
Resistive Load rating per pole	

## defaultTaxonomyAttributeLabel

### Amperage Rating

360A

### Number Of Poles

Three-pole

### Type

Non-reversing

### Coil

110-120 Vac, 50/60 Hz

### Contact configuration

1 NO, 1 NC

### Enclosure

Open with metal mounting plate

### Frame size

15-50 A, two-pole and three-pole

### Inductive full load

360 A

### Model

Contactors

### Resistive load

360 A

### Size

360A, three-pole

### Terminals

Box lugs (posidrive setscrew)

### Connection

Quick

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Drawings

[C25LNE3 2D Drawing Xchange](#)

[C25LNE3 AutoCAD 2D Footprint \(mm\)](#)

[C25LNE3 AutoCAD 2D Footprint](#)

[C25LNE3 2D PDF](#)

[C25LNE3 3D Inventor](#)

[C25LNE3 3D Model Xchange](#)

### Specifications and datasheets

[Eaton Specification Sheet - C25LNE3360A](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)