Eaton C25KNE3200A

Catalog Number: C25KNE3200A

Eaton definite purpose contactor,200A, 110-120 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 200A, Contactor, Three-pole, 200 and 300A, three-pole, 200A, Box lugs (posidrive setscrew), Non-reversing

General specifications

Product Name Eaton definite purpose contactor

UPC 782114183939

Product Height 9.11 in

Product Weight

21.9 lb

Compliances RoHS Compliant

Catalog Notes Resitive Load rating per pole C25KNE3200A Product Length/Depth 7.25 in

Catalog Number

Product Width 7.05 in

Warranty

1 year

Certifications CSA Certified UL Recognized

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Amperage Rating

200A

Number Of Poles

Three-pole

Туре

Non-reversing

Coil 110-120 Vac, 50/60 Hz

Contact configuration 1 NO, 1 NC

Enclosure Open with metal mounting plate

Frame size 15-50 A, two-pole and three-pole

Inductive full load

200 A

Model

Contactor

Resistive load

200 A

Size

200 and 300A, three-pole

Terminals

Box lugs (posidrive setscrew)

Connection

Quick

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings C25KNE3 2D PDF

C25KNE3 2D Drawing Xchange

C25KNE3AutoCAD 2D Footprint (mm)

C25KNE3 3D Inventor

C25KNE3 AutoCAD 2D Footprint

C25KNE3 3D Model Xchange

Specifications and datasheets

Eaton Specification Sheet - C25KNE3200A



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia