Eaton DM1-35022EB-S20S

Catalog Number: DM1-35022EB-S20S

Eaton PowerXL DM1 micro variable frequency drive, Three-phase, 575V, FR4, 15KW, 20HP, IP20, EMI US

Photo is representative

General specifications

Product Name

Eaton PowerXL DM1 micro variable

frequency drive

Catalog Number

DM1-35022EB-S20S

UPC

786689577759

Product Length/Depth

20.5 in

Product Height

11 in

Product Width

10 in

Product Weight

17.3 lb

Certifications

UL Listed



default Taxonomy Attribute LabelBrake chopper Internal brake chopper Series DM1 Drive type General purpose Frame size FR4 **Enclosure rating** IP20 Input phases Three-phase Output phases Three-phase Electromagnetic compatibility filter Yes Internal choke

internal choice

No

Internal line reactor

No

Ambient operating temperature range

-10 to 50 °C CT

-10 to 40 °C VT

Conformal coated boards

Yes

User interface

Multi-segment

Input voltage range

525-600 Vac

Input frequency range

50-60 Hz

Output frequency range

0-400 Hz

Max overload

200 %

Resources

Specifications and datasheets

Eaton Specification Sheet - DM1-35022EB-S20S

Mounting Type DIN rail Panel mount
Digital inputs
Analog inputs 1
Relay outputs 2
Digital outputs 0
High overload (CT) hp 20
High overload (CT) kW
Low overload (VT) kW 18.5
Low overload (VT) amps 27
High overload (CT) amps 22
Low overload (VT) hp 25
Communications onboard Modbus RTU Modbus TCP Ethernet/IP BACnet IP BACnet MS/TP Bluetooth
Communications optional CANopen PROFIBUS SmartWireDT
Motor control modes

V/Hz

Open loop vector control

Fuse size - max

70

Motor type

Induction motor

Permanent magnet motor (SPM/IPM)



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia