

Eaton DM1-35010EB-S20S

Catalog Number: DM1-35010EB-S20S

Eaton PowerXL DM1 micro variable frequency drive, Three-phase, 575V, FR2, 5.5KW, 7.5HP, IP20, EMI US

General specifications

Product Name	Catalog Number
Eaton PowerXL DM1 micro variable frequency drive	DM1-35010EB-S20S
	UPC
	786689577940
Product Length/Depth	Product Height
109 mm	220 mm
Product Width	Product Weight
180 mm	2.63 kg
Certifications	
UL Listed	

[Brake chopper](#)

Internal brake chopper

[Series](#)

DM1

[Drive type](#)

General purpose

[Frame size](#)

FR2

[Enclosure rating](#)

IP20

[Input phases](#)

Three-phase

[Output phases](#)

Three-phase

[Electromagnetic compatibility filter](#)

Yes

[Internal choke](#)

No

[Internal line reactor](#)

No

[Ambient operating temperature range](#)

-10 to 50 °C CT

-10 to 40 °C VT

[Conformal coated boards](#)

Yes

[User interface](#)

Multi-segment

[Input voltage range](#)

525-600 Vac

[Input frequency range](#)

50-60 Hz

[Output frequency range](#)

0-400 Hz

[Max overload](#)

200 %

[Specifications and datasheets](#)

Eaton Specification Sheet - DM1-35010EB-S20S

Fuse size - max

40

Mounting Type

DIN rail

Panel mount

Digital inputs

4

Analog inputs

1

Relay outputs

2

Digital outputs

0

High overload (CT) hp

7.5

High overload (CT) kW

5.5

Low overload (VT) kW

7.5

Low overload (VT) amps

13.5

High overload (CT) amps

10

Low overload (VT) hp

10

Communications onboard

Modbus RTU

Modbus TCP

Ethernet/IP

BACnet IP

BACnet MS/TP

Bluetooth

Communications optional

CANopen

PROFIBUS

SmartWireDT

Motor control modes

V/Hz

Open loop vector control

Motor type

Induction motor

Permanent magnet motor (SPM/IPM)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)