

Eaton E51BLT56PU

Catalog Number: E51BLT56PU

Eaton E51 NEMA limit switch inductive proximity sensor, Limit switch style, Factory Sealed 6P+ Inductive Proximity Top Sensor Enclosure, Sensor dist 24 mm, 500 mA max AC/DC, 2-Wire AC, NC, 500 mA AC/DC SS Output



General specifications

Product Name	Catalog Number
Eaton E51 NEMA limit switch inductive proximity sensor	E51BLT56PU
	UPC
	782113866178
Product Length/Depth	Product Height
1.54 in	2 in
Product Width	Product Weight
1.58 in	1.1313 lb
Warranty	Certifications
1 year	UL Listed CSA Certified

Catalog Notes

Sensor head is hard wired to sensor body and cannot be detached; but can be unfastened and rotated to any of four positions.

defaultTaxonomyAttributeLabel

Contact Rating

500 mA AC/DC Solid State Output

Actuator function

Unshielded

Cable type

SOOW-A

Accuracy

< 0.3%

Enclosure material

Housing: die cast zinc

Head: plastic

Connection

8 ft (2.4 m) cable

Contact configuration

2-wire AC, NC

Sensor type

Inductive proximity

Environmental rating

NEMA 3, NEMA 3S, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P,
NEMA 12, NEMA 13, IP68

Cord length

8 ft

Operating temperature - max

158 °F

Operating temperature - min

-13 °F

Maximum AC current

500 mA

Maximum DC current

500 mA

Input voltage

20-264 Vac/dc

LED indicator

Output status: yellow

Power on: green

Resources

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - E51BLT56PU](#)

Protection

Short circuit protected



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia