

CWPS Wall Packs

40W/60W/80W | 3CCT | 120-347V

Budget-friendly, versatile & slim wall pack that fits virtually all outdoor general purpose lighting applications. Large footprint gives the coverage you need to replace old legacy wall packs!

Classic Look With a Slim
Redesign and Large Footprint
retrofit friendly



Colour Selectable
3000K / 4000K / 5000K

Built-in Photocell

Power Selectable
40W / 60W / 80W

120-347V
Universal Driver
0-10V dimming

Wet Location Rated
IP65

Borosilicate Glass Lens Resists Thermal
Expansion, Stress, and is Chemical Resistant
will never yellow

TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	10,321 lm
Efficacy	129.88 lm/W
CCT	3000K/4000K/5000K
CRI	82
Beam Angle	105°
Dimmable	0-10V
L70 Life	>54,000 hrs
Warranty	10-year

LUMEN OUTPUT			
	3000K	4000K	5000K
40W	5480 lm	5650 lm	5831 lm
60W	7979 lm	8321 lm	8459 lm
80W	10321 lm	10942 lm	10605 lm

APPROVALS & LISTINGS

cUL	E482965
DLC Premium	S-CEQMFO

DIMENSIONS AND WEIGHTS

Fixture Weight	7.26 lbs
Fixture Dimensions	13.81 x 8.88 x 4.48 in
Carton Qty	1
Carton Weight	9.24 lbs
Carton Dimensions	15.1 x 10.6 x 6.5 in

ELECTRICAL

Wattage	40W/60W/80W
Voltage	120-347V
Current	0.85A
Surge Protection	6kV
Auxiliary Output	12V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 45°C

CONSTRUCTION

Cord Whip	13.78"
Housing	Die-cast Aluminum
Lens	Glass
Finish	Powder Coated
Finish Colour	Bronze
IP Rating	IP65

DIMENSIONAL DRAWINGS (IN)

