Outdoor Power Products by Midwest

Midwest supplies the finest quality weatherproof electrical equipment.



Power outlets

Power outlets provide one or more receptacles, with or without overcurrent protection, in a single enclosure. They eliminate the need for several separately mounted components while providing maximum protection against the weather and normal field use. See page 29.



Temporary power/power outlets Temporary power equipment combines all the required components to supply power to the various construction trades. This may include receptacles, overcurrent protection, a meter socket and GFCIs, all designed for outdoor installation. See page 30.



RV power outlets

For use in recreational vehicle parks, RV power outlets provide user safety, rugged construction, weather protection, receptacle versatility and attractive looks. Both metallic and thermoplastic enclosures are available, and options include metering, TV/telephone and lighting. See page 31.



Service equipment

Midwest offers a range of service equipment for single family residences and mobile homes that meet NEC and UL requirements. They are factory assembled and wired with loop feed lugs to speed installation time. See page 31.



Spa panels Spa panels offer a low-cost means to meet NEC requirements for a GFCI disconnect for spas, hot tubs and swimming pools. See page 31.

All Midwest Electric products:

- Are made from G90 galvanized (zinc-coated) steel or thermoplastic enclosures for maximum corrosion protection
- Feature the highest quality electrical components
- Are designed and manufactured with user protection in mind

Amps	Volts	Circuit Protection	Receptacles	Dimensions			Cat No
				Н	W	D	Cat. No.
20	120	-	5-20RGFI	7 1/8	5 3/4	5 3/16	U010010GRP
		SPST Switch	5-20RGFI	7 1/8	5 3/4	5 3/16	U010S010GRP
		-	(2) 5-20RGFI	7 1/8	5 3/4	5 3/16	U012010GRP


Back yard power outlets (green enclosures)


RV power outlets (gray enclosures)


Amps	Volts	Circuit Protection	Receptacles	Dimensions			Cat. No.
				Н	W	D	Cut. No.
30	120	-	R32U	7 1/8	5 3/4	5 3/16	U013P
		CB130	R32U	9 1/8	5 3/4	5 3/16	U013CP
30	120/240	-	R32U, 5-20R2	9 1/8	5 3/4	5 3/16	U041P
50	120	-	14-50R	7 1/8	5 3/4	5 3/16	U054P
70	120/130	CB120, CBN130, Space, CB120	R32U, 20R2	14 3/8	7 1/4	5 3/16	U041CP

Power outlets with timers (green enclosures)

Amps	Volts	Receptacles	Cabinet Size	Cat. No.
20	125	5-20R2GFCI + 12-hour timer	5" × 7"	T3010GRP
15	125	5-20R2GFCI + 24-hour timer	5" x 7"	T4010GRP
15	120	5-20R2GFCI + 7-day digital timer	5" x 7"	T5010GRP







U010010GRP





U013P



U010S010GRP

U013CP





œ

Æ











T3010GRP



T4010GRP



T5010GRP