

Eaton E57-30GU15-A1AB

Catalog Number: E57-30GU15-A1AB

Eaton E57 inductive proximity sensor, Two-Wire Series, Tubular, 1.18 dia, Straight, Sensor dist: 15 mm, 200 mA max AC, 2 - Wire DC, NC, 200 mA at 250 Vac, 3 Pin Dual Key Micro Connector, 20-250 Vac input, < 3% accuracy, None, Un-shielded

General specifications



Photo is representative

Product Name	Catalog Number
Eaton E57 inductive proximity sensor	E57-30GU15-A1AB
UPC	Product Length/Depth
786685535920	1.18 in
Product Height	Product Width
1.5 in	1.18 in
Product Weight	Warranty
0.3 lb	1 year
Compliances	Certifications
CE Marked	UL Listed CSA Certified

defaultTaxonomyAttributeLabel

Contact Rating

200 mA at 250 Vac

Actuator function

Unshielded

Accuracy

< 3%

Enclosure material

Nickel plated brass

Connection

3-pin dual key micro connector

Contact configuration

2-wire DC, NC

Series

E57

Sensor type

Inductive proximity

Environmental rating

IP67, IP69K

Operating temperature - max

158 °F

Operating temperature - min

-13 °F

Maximum AC current

200 mA

Input voltage

20-250 Vac

LED indicator

Output status: red

Protection

None

Resources

Brochures

[Global Series inductive proximity sensors](#)

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

[Product Range Catalog Sensors – products, basic information, applications](#)

Multimedia

[We make what matters](#)

Specifications and datasheets

[Eaton Specification Sheet - E57-30GU15-A1AB](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)