

Eaton FH20

Catalog Number: FH20

Eaton A200/B100 heater, Used with Starter Sizes 0,1, and 2, A200/B100 Heater, NEMA, Ambient 1.35-1.47, 1.56-1.71A, Non-Comp 1.26-1.37, 1.53-1.67A, Used with Starter Sizes 0,1, and 2, Type A and B, Thermal and Fast Trip



Photo is representative

General specifications

| | |
|----------------------------|--|
| Product Name | Catalog Number |
| Eaton A200/B100 heater | FH20 |
| UPC | Product Length/Depth |
| 786678629476 | 2.1 in |
| Product Height | Product Width |
| 0.8 in | 1.3 in |
| Product Weight | Warranty |
| 0.03 lb | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |
| Certifications | Catalog Notes |
| CSA Certified UL Listed | Select heater coils based on full load current(FLA) shown on motor nameplate. Heater coils are rated to protect 40 degree C rise and a service factor of 1.15, Single-Phase requires 2 heaters, Three-Phase Requires 3 heaters |

[Special features](#)

Used with Starter Sizes 0,1, and 2

[Type](#)

A200/B100 Heater

[Used with](#)

Used with Starter Sizes 0,1, and 2

[Design](#)

NEMA

[Full load current range](#)

Ambient 1.35-1.47, 1.56-1.71 A, Non-Comp 1.26-1.37, 1.53-1.67
A

[Overload relay](#)

Type A and B

[Trip type](#)

Thermal and fast trip

[Catalogs](#)

[Eaton's Volume 5—Motor Control and Protection](#)

[Installation instructions](#)

[Instructions for A200, A210, A250 size 6, two- or three-pole non-reversing or reversing motor controllers](#)

[Specifications and datasheets](#)

[Eaton Specification Sheet - FH20](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)