

# Eaton P60G28T15CUB

Catalog Number: P60G28T15CUB

Eaton Mini-Power Center, Three-phase, PV: 600V, Taps: 2 at -5% FCBN, SV: 208Y/120V, Indoor-Outdoor, 115°C, 15 kVA, Cu windings , Frame: 289A



Photo is representative

## General specifications

### Product Name

Eaton Mini-Power center

### Catalog Number

P60G28T15CUB

### UPC

786680034787

### Product Length/Depth

9.38 in

### Product Height

36.12 in

### Product Width

28.75 in

### Product Weight

401 lb

### Warranty

Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Compliances

NEMA Compliant

### Certifications

UL Listed

ANSI

CSA Certified

IEEE Certified

### Catalog Notes

All copper construction (coil and interior) and accepts bolt-on branch breakers from the BAB family

## Physical Attributes

### Coil material

Copper

### Enclosure

NEMA 3R

### Frame

289A

### Tap size

2 at -5% FCBN

### Type

Mini-power center

### Wiring connection

105D15K

## Performance Ratings

### Frequency rating

60 Hz

### Phase

Three-phase

### Primary voltage

600 V

### Secondary Voltage

208Y/120 V

### Temperature rise

115 °C rise

### Volt ampere rating

15 kVA

## Miscellaneous

### Weathershield

Indoor-Outdoor

## Resources

### Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

### Multimedia

[Eaton's Transformer Flex Center](#)

### Specifications and datasheets

[Eaton Specification Sheet - P60G28T15CUB](#)

### Warranty guides

[Selling Policy 25-000 - Distribution and Control Products and Services](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)