

Eaton XTCR009B21A

Catalog Number: XTCR009B21A

Eaton XT IEC contactor, 9A, 110 Vac 50 Hz, 120 Vac 60 Hz, 2NO-2NO, 9A, Frame B, 45 mm, 50-60 Hz, 0.5, 1.5/ 3, 3, 5, 7.5 hp (1/3PH @ 115, 230/200, 230, 460, 575 V), Three-pole, Reversing, , Screw terminals, FVR

General specifications



Product Name
Eaton XT IEC contactor

Catalog Number
XTCR009B21A

UPC
786685180298

Product Length/Depth
3.5 in

Product Height
4 in

Product Width
5.5 in

Product Weight
1.2 lb

Compliances
CE Marked
RoHS Compliant

Certifications
UL Listed
CSA Certified
IEC 60947
EN 60947

Catalog Notes
Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

defaultTaxonomyAttributeLabel

Amperage Rating

9A

HP rating - max

0.5, 1.5/ 3, 3, 5, 7.5 hp (1/3PH @115,230/200,230,460,575 V)

Number Of Poles

Three-pole

Type

Full voltage reversing contactor

Frequency rating

50-60 Hz

Terminals

Screw terminals

Coil voltage

110-120 Vac, 50/60 Hz

Contact configuration

2 NO, 2 NO

Continuous ampere rating

9 A

Series

XT IEC

Operation

Reversing

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTCR_B 3D Inventor](#)

[XTCR_B AutoCAD 2D Footprint](#)

[XTCR_B AutoCAD 2D Footprint \(mm\)](#)

[XTCR_B 2D Drawing Xchange](#)

[XTCR_B 2D PDF](#)

[XTCR_B 3D Model Xchange](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCR009B21A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)