

# Eaton DG1-35125FN-C21C

Catalog Number: DG1-35125FN-C21C

Eaton PowerXL DG1 variable frequency drive, 525-600V input 90 kW 125 Hp CT 3PH 50/60 Hz 125A output IP21/type 1 enclosure FR6 LCD Internal EMC filter and DC choke EtherNet, RS-485, BACnet MS/TP, Modbus TCP and RTU ports 2 exp slots

## General specifications



<b>Product Name</b>	<b>Catalog Number</b>
Eaton PowerXL DG1 variable frequency drive	DG1-35125FN-C21C
	<b>UPC</b>
	786685975481

<b>Product Length/Depth</b>	<b>Product Height</b>
14.96 in	38.19 in

<b>Product Width</b>	<b>Product Weight</b>
14.96 in	172 lb

<b>Warranty</b>	<b>Compliances</b>
Eaton Selling Policy 25-000 generally applies with some exceptions. Drive products come with a standard 24 months from date of shipment and 36 months with Eaton certified start up all inclusive coverage parts labor and travel.	RoHS Compliant C-Tick Compliant CE Marked GoST-R

<b>Certifications</b>
cUL Listed UL Listed UL 508C EN ISO 13849-1 EN 62061 IEC 61508

## defaultTaxonomyAttributeLabel

### Brake chopper

No brake chopper

### Horsepower

125 hp

### Phase

Three-phase in, three-phase out

### Protection filtering

Internal EMC filter and DC choke

### Special features

Coated boards

### Frequency rating

50-60 Hz

### Frame size

6

### Keypad

Included

### Input voltage

575 V, 525-600 V(-15%, +10%)

### Display

LCD graphical

### Torque rating

CT

### Communication

EtherNet, RS-485, BACnet MS/TP, Modbus TCP and RTU communication

### Enclosure

IP21/type 1

### Protection

Internal EMC filter, DC choke

### Output current - max

125 A

### Software

Active energy control, quick start wizard

### Number of slots

2 expansion slots

## Resources

### Application notes

Operating at low temperatures

PID controller

DG1 in pump and fan applications

Electromagnetic compatibility (EMC)

Connecting drives to generator supplies

Dual Rating What exactly does that mean?

Starting, stopping and operation

Analog I/Os

Digital I/Os

Torque control

Smoke Mode and fire mode

Load balancing in multi motor applications

Real time clock and use of the timers

Motor data and V/f curves

### Catalogs

Product Datasheet - DG1-35125FN-C21C

Product Range Catalog Drives Engineering

### Multimedia

PowerXL DG1 Variable Frequency Drive - Setup via WebUI

Power XL General Purpose Drives

### Specifications and datasheets

Eaton Specification Sheet - DG1-35125FN-C21C

#### Material

Coated board

#### Power consumption

90 kW

#### Electromagnetic compatibility filter

EMC Filter

#### Internal DC choke

Yes

#### Conformal coated boards

Yes

#### User interface

Graphical Keypad

#### High overload (CT) amps

125 A

#### High overload (CT) kW

90 kW

#### High overload (CT) hp

125 hp

#### Low overload (VT) amps

144 A

#### Low overload (VT) kW

110 kW

#### Low overload (VT) hp

150 hp

#### Input voltage range

525 - 600 V

#### Input frequency range

50 - 60 Hz

#### Output frequency range

0 - 400 Hz

#### Max overload

110% for 1 minute

#### Recommended fuse size

200

#### Communications onboard

EtherNet/IP, Modbus TCP, RS-485: Modbus RTU, BACnet

MS/TP

Motor control modes

Frequency, Speed, Open-loop speed, Open-loop torque

Motor type

Inductio, PM (IPM & SPM)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)