



Connecting terminal, 35 mm<sup>2</sup> according to UL 489, 480Y/277V for LS 5SJ4...-HG Infeed LS

Model	
product brand name	SENTRON
product designation	Connecting terminal
design of the product	35 mm <sup>2</sup> , acc. to UL 489, 480Y/277 V for MCBs 5SJ4...-HG infeed MCB
Supply voltage	
operating voltage at AC rated value	1 000 V
Connections	
tightening torque	
• minimum	4 N·m
• maximum	4 N·m
type of connectable conductor cross-sections for copper conductor stranded	2.5 - 35 mm <sup>2</sup>
Mechanical Design	
height	31.1 mm
width	16.2 mm
depth	25.7 mm
length	74.7 mm
net weight	33.6 g
Approvals Certificates	
General Product Approval	



[Confirmation](#)



[Miscellaneous](#)



other	Environment
<p><a href="#">Confirmation</a></p> <p><a href="#">Miscellaneous</a></p>	<p><a href="#">Environmental Confirmations</a></p>

**Further information**

Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>  
 Information- and Downloadcenter (Catalogs, Brochures,...)  
<http://www.siemens.com/lowvoltage/catalogs>  
 Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mifb=5ST3666-0HG>  
 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/5ST3666-0HG>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)  
[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=5ST3666-0HG](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5ST3666-0HG)

**CAX-Online-Generator**  
<http://www.siemens.com/cax>

**Tender specifications**  
<http://www.siemens.com/specifications>





