



Connecting terminal, 50 mm² according to UL 489, 480Y/277V for LS 5SJ4...-HG Infeed busbar

Model	
product brand name	SETRON
product designation	Connecting terminal
design of the product	50 mm ² , acc. to UL 489, 480Y/277 V for MCBs 5SJ4...-HG infeed busbar
Supply voltage	
operating voltage at AC rated value	1 000 V
Connections	
tightening torque	
• minimum	2 N·m
• maximum	3.5 N·m
type of connectable conductor cross-sections for copper conductor stranded	2.5 - 50 mm ²
Mechanical Design	
height	51 mm
width	17.75 mm
length	31.2 mm
net weight	33 g
Approvals Certificates	
General Product Approval	



EG-Konf.

[Confirmation](#)



UR


[Miscellaneous](#)



other	Environment
Miscellaneous	Confirmation Environmental Confirmations

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
 Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
 Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3666-2HG>
 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/5ST3666-2HG>
 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



last modified:

3/12/2024 

