SIEMENS

Data sheet

6GK1901-1BB30-0AB0

product type designation

product description



IE FC RJ45 Plug 145 (2x2)

RJ45 data connector

Industrial Ethernet FastConnect RJ45 plug 145 2x 2, RJ45 plug-in connector (10/100 Mbit/s) with rugged metal enclosure and FC connection system, for IE FC TP cable 2x 2; 145° cable outlet 1 pack = 10 units.

suitability for use	For connection to IE FC TP cables 2x2, suitable for fast assembly with the FastConnect system	
transfer rate		
transfer rate / for Industrial Ethernet	10 Mbit/s, 100 Mbit/s	
interfaces		
number of electrical connections		
 for Industrial Ethernet FC TP cables 	4	
 for network components or terminal equipment 	1	
type of electrical connection		
• for Industrial Ethernet FC TP cables	integrated cut-and-clamp contacts for 4-wire TP FC installation cable AWG22	
 for network components or terminal equipment 	RJ45 connector	
type of electrical connection / FastConnect	Yes	
mechanical data		
material / of the enclosure	metal	
number of reuses	10	
locking mechanism design	other	
design, dimensions and weights		
type of cable outlet	145° cable outlet	
width	13.9 mm	
height	16 mm	
depth	55.6 mm	
net weight	35 g	
connectable cable cross-section	6.5 6.5 mm	
connectable conductor cross-section	0.33 mm ²	
ambient conditions		
ambient temperature		
during operation	-40 +85 °C	
during storage	-40 +85 °C	
during transport	-40 +85 °C	
relative humidity		
at 25 °C / without condensation / during operation / maximum	95 %	
protection class IP	IP20	
product features, product functions, product components / general		
product feature		
 PoE capability 	Yes	
 PoE+capability 	Yes	
• silicon-free	Yes	

product component		
strain relief	Yes	
standards, specifications, approvals		
certificate of suitability		
 RoHS conformity 	Yes	
 UL approval 	Yes	
 cULus approval 	Yes	
railway application in accordance with EN 50155	No	
standard for structured cabling	Cat5	
standards, specifications, approvals / Environmental Product Declaration		
Environmental Product Declaration	Yes	
Global Warming Potential [CO2 eq]		
• total	0.277 kg	
during manufacturing	0.263 kg	
during operation	0.0086 kg	
after end of life	0.0062 kg	
further information / internet links		
internet link		
• to website: Image database	https://www.automation.siemens.com/bilddb	
• to website: Industry Online Support	https://support.industry.siemens.com	
security information		
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)	

Approvals / Certificates

General Product Approval

Marine / Shipping



Manufacturer Declara-tion

Declaration of Conformity

Miscellaneous





Marine / Shipping

Environment

Industrial Communication



Confirmation



PROFINET

last modified:

3/23/2024

