



Ceramalux Non-ALTO

C100S54/M PH 12PK

Philips Ceramalux lamps provide efficient lighting solutions for industrial applications, warehouses, post top applications and parking lots.

Product data

| General Information | |
|------------------------------------|-----------------------------------|
| Cap-Base | E26 [Single Contact Medium Screw] |
| Operating Position | UNIVERSAL [Any or Universal (U)] |
| Light Technical | |
| Chromaticity Coordinate X (Nom) | 520 |
| Chromaticity Coordinate Y (Nom) | 420 |
| Correlated Color Temperature (Nom) | 2100 K |
| Luminous Efficacy (Rated) (Min) | 84 lm/W |
| Luminous Efficacy (rated) (Nom) | 92 lm/W |
| Color rendering index (CRI) | 18 |
| Operating and Electrical | |
| Power Consumption | 100.4 W |
| Lamp Current (Nom) | 2.1 A |
| Voltage (Nom) | 55 V |
| Voltage (Nom) | 55 V |
| Mechanical and Housing | |
| Bulb Finish | Clear |

| Bulb Material | Hard Glass |
|---------------------------------|-------------------|
| Bulb Shape | BD17 |
| Approval and Application | |
| Mercury (Hg) Content (Max) | 22 mg |
| Product Data | |
| Order product name | C100S54/M PH 12PK |
| Full product name | C100S54/M PH 12PK |
| Order code | 467274 |
| Material Nr. (12NC) | 928601143590 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 046677467272 |
| Numerator - Packs per outer box | 12 |
| EAN/UPC - Case | 50046677467277 |

Ceramalux Non-ALTO

Dimensional drawing

| Product | D | C (max) |
|-------------------|-------|---------|
| C100S54/M PH 12PK | 55 mm | 138 mm |

