

Eaton DILM9-10(600V60HZ)

Catalog Number: DILM9-10(600V60HZ)

Eaton XT IEC mini contactor, 9A, 600 Vac, 60 Hz, 1NO, 9A, Frame B, 45 mm, 60 Hz, 0.5, 1.5/ 3, 3, 5, 7.5 (1/3PH @120, 240/208, 240, 480, 575 V), Three-pole, Screw terminals, Full voltage non-reversing miniature contactor, 4 kW

General specifications



Product Name	Catalog Number
Eaton XT IEC mini contactor	DILM9-10(600V60HZ)
EAN	Product Length/Depth
4015082766856	1.8 in
Product Height	Product Width
2.7 in	3 in
Product Weight	Warranty
0.48 lb	1 year
Compliances	Certifications
CE Marked	EN 60947
RoHS Compliant	CSA Certified
	IEC 60947
	UL Listed

Catalog Notes

Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

defaultTaxonomyAttributeLabel

Amperage Rating

9A

HP rating - max

0.5, 1.5/ 3, 3, 5, 7.5 (1/3PH @120,240/208,240,480,575 V)

Number Of Poles

Three-pole

Type

Full voltage non-reversing miniature contactor

Frequency rating

60 Hz

Frame size

45 mm

Terminals

Screw terminals

Coil

600 Vac, 60 Hz

Coil voltage

600 Vac, 60 Hz

Contact configuration

1 NO

Continuous ampere rating

9 A

Series

XT IEC

Operation

Non-reversing

Power consumption

4 kW

Resources

Multimedia

[Contactors Explained](#)

[S1. E4. Ask the Experts - NEMA, IEC and DP contactors](#)

Specifications and datasheets

[Global Data Sheet - DILM9-10\(600V60HZ\)](#)

[Eaton Specification Sheet - DILM9-10\(600V60HZ\)](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)