

Eaton DH1-35022FB-C54C

Catalog Number: DH1-35022FB-C54C

Eaton PowerXL DH1 VFD,22A,20 HP,15 kW,525 - 600 Vac,KEYPAD,EMC Filter,DC Choke,Brake Chopper,IP54



General specifications

Product Name	Catalog Number
Eaton PowerXL DH1 variable frequency drive	DH1-35022FB-C54C
	UPC
	786689049539
Product Length/Depth	Product Height
16.5 in	9.63 in
Product Width	Product Weight
6.61 in	23.37 lb
Warranty	Compliances
Eaton Selling Policy 25-000 generally applies with some exceptions. Drive products come with a standard 24 months from date of shipment and 36 months with Eaton certified start up all inclusive coverage parts labor and travel.	CE Marked RoHS Compliant C-Tick Compliant GoST-R
	Certifications
	IEC 61508 cUL Listed EN ISO 13849-1 UL Listed UL 508C EN 62061

defaultTaxonomyAttributeLabel

Amperage Rating

22A

Horsepower

20 hp

Voltage rating

575 V

Keypad

Included

Power consumption

15 kW

Series

DH1

Electromagnetic compatibility filter

EMC

Internal DC choke

Yes

Conformal coated boards

Yes

User interface

Graphical Keypad

Low overload (VT) amps

22A

Low overload (VT) kW

15 kW

Low overload (VT) hp

20 HP

Input voltage range

525 - 600 Vac

Input frequency range

50 - 60 Hz

Output frequency range

0 - 400 Hz

Max overload

110% for 1 minute

Recommended fuse size

Resources

Catalogs

[Adjustable Frequency Drives](#)

Specifications and datasheets

[Eaton Specification Sheet - DH1-35022FB-C54C](#)

35A

Relay outputs

3

Communications onboard

BACnet/IP, Modbus TCP, Modbus RTU, BACnet MS/TP

Communication interface

PROFIBUS-DP

Motor control modes

Frequency Control, Speed Control, Open Loop Speed Control,
Open Loop Torque Control

Motor type

Induction



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)