

# Eaton DG1-35052FB-C54C

Catalog Number: DG1-35052FB-C54C

Eaton PowerXL DG1 variable frequency drive, 525-600V input 37 kW 50 Hp CT 3PH 50/60 Hz 52A output IP54/type 12 FR5 LCD Internal EMC filter and DC choke EtherNet, RS-485, BACnet MS/TP, Modbus TCP and RTU ports 2 exp slots Brake chopper

## General specifications



### Product Name

Eaton PowerXL DG1 variable frequency drive

### Catalog Number

DG1-35052FB-C54C

### UPC

786685975306

### Product Length/Depth

17 in

### Product Height

28 in

### Product Width

15 in

### Product Weight

92 lb

### Warranty

Eaton Selling Policy 25-000 generally applies with some exceptions. Drive products come with a standard 24 months from date of shipment and 36 months with Eaton certified start up all inclusive coverage parts labor and travel.

### Compliances

RoHS Compliant  
CE Marked  
C-Tick Compliant  
GoST-R

### Certifications

cUL Listed  
UL Listed  
UL 508C  
EN ISO 13849-1  
EN 62061  
IEC 61508

## defaultTaxonomyAttributeLabel

### Brake chopper

Brake chopper

### Horsepower

50 hp

### Phase

Three-phase in, three-phase out

### Protection filtering

Internal EMC filter and DC choke

### Special features

Coated boards

### Frequency rating

50-60 Hz

### Frame size

5

### Keypad

Included

### Input voltage

575 V, 525-600 V(-15%, +10%)

### Display

LCD graphical

### Torque rating

CT

### Communication

EtherNet, RS-485, BACnet MS/TP, Modbus TCP and RTU communication

### Enclosure

IP54/type 12

### Protection

Internal EMC filter, DC choke

### Output current - max

52 A

### Software

Active energy control, quick start wizard

### Number of slots

2 expansion slots

## Resources

### Application notes

Motor data and V/f curves

DG1 in pump and fan applications

Operating at low temperatures

Real time clock and use of the timers

Digital I/Os

Dual Rating What exactly does that mean?

Starting, stopping and operation

Load balancing in multi motor applications

Smoke Mode and fire mode

Torque control

PID controller

Connecting drives to generator supplies

Analog I/Os

Electromagnetic compatibility (EMC)

### Catalogs

Product Range Catalog Drives Engineering

Product Datasheet - DG1-35052FB-C54C

### Multimedia

Power XL General Purpose Drives

PowerXL DG1 Variable Frequency Drive - Setup via WebUI

### Specifications and datasheets

Eaton Specification Sheet - DG1-35052FB-C54C

#### Material

Coated board

#### Power consumption

37 kW

#### Electromagnetic compatibility filter

EMC Filter

#### Internal DC choke

Yes

#### Conformal coated boards

Yes

#### User interface

Graphical Keypad

#### High overload (CT) amps

52 A

#### High overload (CT) kW

37 kW

#### High overload (CT) hp

50 hp

#### Low overload (VT) amps

62 A

#### Low overload (VT) kW

45 kW

#### Low overload (VT) hp

60 hp

#### Input voltage range

525 - 600 V

#### Input frequency range

50 - 60 Hz

#### Output frequency range

0 - 400 Hz

#### Max overload

110% for 1 minute

#### Recommended fuse size

80

#### Communications onboard

EtherNet/IP, Modbus TCP, RS-485: Modbus RTU, BACnet

MS/TP

Motor control modes

Frequency, Speed, Open-loop speed, Open-loop torque

Motor type

Inductio, PM (IPM & SPM)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)