



Slim Flood LED (TF)

Slim Flood, 100W, 4000K, Generation 1, Yoke mount, 120-277VAC, Bronze finish

Slim Flood, 100W, 4000K, Generation 1, Yoke mount, 120-277VAC, Bronze finish - 125 lm/W

Slim Flood LED Floodlights are your best value for discreet and modern design on your floodlighting projects. Versatile and stylish with six different sizes to choose from, Slim Flood provides application flexibility for ground, wall, or pole mount installations. Ideal for sign lighting, building facades, security lighting, and general purpose floodlighting applications. The discreet low profile design will not interfere with your landscape layouts.

Product data

General information		Material	
Lamp Source Code	LED	Material	Aluminum
Colour Temperature	4000 K	Enclosure	Metal and Plastic
CRI	80	Approval and application	
Photometric Distribution Type	Flood	Safety Listing	ETL
Mounting	Surface Ground / Floor Wall	Energy Certifications	DLC Standard cETLus
Number Of Pieces	1	IP Rating	IP65 [Dust penetration-protected, jet-proof]
Grade	Value Grade	Vibration Rating	1.5G
Operating and electrical		Initial performance (IEC compliant)	
Voltages	120/208/240/277 V	Luminaire Lumens	12439
Luminaire Input Watts	100	Efficacy	125 lm/W
Conduit Connection	7/8 inch knockout	Application conditions	
Mechanical and housing		Ambient temperature range	-40 °C to 40 °C
Shape	Rectangular	Max Ambient Temp	40 °C

Slim Flood LED (TF)

Min Ambient Temp	-40 °C
Min Ambient Temp-DUP(do not use)	-40 °C
Product data	
Full product code	911401733622
Order product name	TF100-NW-G1-Y-FL-8-BZ
EAN/UPC - Product	783352025975
Order code	TF100-NW-G1-Y-FL-8-BZ
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	4
Material Nr. (12NC)	911401733622
Net Weight (Piece)	3.180 kg
Catalog Number	TF100-NW-G1-Y-FL-8-BZ
Catalog Number Description	Slim Flood, 100W, 4000K, Generation 1, Yoke mount, 120-277VAC, Bronze finish

