



FORUM Essential



DELIVERED

1'×4': Up to 5000 lm (40W) 2'×2': Up to 5000 Im (40W) 2'×4': Up to 6250 Im (50W)

COLOR TEMPERATURE



Selectable 35, 40, 50 K

SIZE

[1'x4'] [2'x2'] [2'x4']

WATTAGE



20W, 30W, 40W or 30W, 40W, 50W*

FEATURES

- Efficient back-lit technology
- Industry standard 0-10V dimmers
- Flicker < 5%
- 125 lm/W
- Color temperature selectable switch on the driver (35 K, 40 K, and 50 K)
- 110° beam spread
- 80+ CRI
- LED driver with 120-347 AC
- Easy mounting in T-bar ceilings with standard dimensions
- Suitable for damp locations
- I.C. rated



ACCESSORIES



XTLRB-14-WH-FKT

SURFACE MOUNT KIT FOR USE WITH 1'×4' FORUM ESSENTIAL PANELS. CONSULT FACTORY FOR ADDITIONAL COLORS.



XTLRB-22-WH-FKT

SURFACE MOUNT KIT FOR USE WITH 2'×2' FORUM ESSENTIAL PANELS. CONSULT FACTORY FOR ADDITIONAL COLORS.



XTLRB-24-WH-FKT

SURFACE MOUNT KIT FOR USE WITH 2'×4' FORUM ESSENTIAL PANELS. CONSULT FACTORY FOR ADDITIONAL COLORS.

LITELINE.COM

*1'×4' & 2'×2' available in 20W/30W/40W, 2'×4' available in 30W/40W/50W.

M-FORUMESSENTIAL-SS-E

