

**OCC** Portable Construction Heater

**OCC-WB** Unit Heater with Bracket

**OCC-RF** Hard-Wired Unit Heater



Grounded 3-Pronged Outlet (OCC, OCC-WB)



NEMA 6-30R  
30A, 250VAC

### Features

**Color**

- Standard: almond.

**Finish**

- Standard: epoxy/polyester powder paint.

**Voltage**

- 240/208V, 1-phase.

**Construction**

- Handle may be used as a reel for the electric cable and as attach point for the bracket.
- 6 ft. (2 m) molded electric cable.
- Safely recessed thermostat knob reduces heater size to a minimum.

- High-limit temperature control with automatic reset.

**Fan**

- 300 cfm fan.

**Heating element**

- Helical coil nickel-chromium alloy wire protected by ceramic insulators.
- Heating element provides instant heat.

**Temperature rise**

- 28 °C (51 °F).

**Control**

- Built-in thermostat included.

### Features OCC

**Fan**

- Totally enclosed motor (-MF model).
- Open motor (-MO model).

*Note: The open motor is not intended for use in a dusty environment.*

**Installation**

- Must be plugged into a grounded 3-pronged outlet, 30A, 250VAC.

*Note: Always unplug heater when not in use.*

**Warranty**

- 2-year warranty against defects (-MO model).
- 3-year warranty against defects (-MF model).

**Application**

- Construction area, workshop, garage

### Features OCC-WB

**Fan**

- Open motor.

*Note: The open motor is not intended for use in a dusty environment.*

**Installation**

- Wall or ceiling mounting using the supplied bracket which allow 360° rotation of the heater and prevent it from tipping over.
- Must be plugged into a grounded 3-pronged outlet, 30A, 250VAC.

*Note: Always unplug heater when not in use.*

**Warranty**

- 2-year warranty against defects.

**Application**

- Workshop, shed, garage.

### Features OCC-RF

**Fan**

- Open motor.

*Note: The open motor is not intended for use in a dusty environment.*

**Installation**

- Hard-wired into an electrical junction box (not included).
- Wall or ceiling mounting using the supplied bracket which allow 360° rotation of the heater and prevent it from tipping over.

**Warranty**

- 2-year warranty against defects.

**Application**

- Workshop, shed, garage.

### Models

Watts	Volts	Product # <sup>1</sup>	Motor type	Grounded 3-pronged outlet	Weight lb	kg
4800/3600	240/208	OCC4800AM-MF-TB6	Enclosed	30A, 250VAC	16.0	7.3
4800/3600	240/208	OCC4800AM-MO-TB6	Open	30A, 250VAC	16.0	7.3
4800/3600	240/208	OCC4800AMWB-MO-TB6 <sup>1</sup>	Open	30A, 250VAC	16.0	7.3
4800/3600	240/208	OCC4800AMRF-MO-TB6 <sup>1</sup>	Open	-	16.0	7.3

<sup>1</sup> Mounting bracket included.  
Standard color is almond.

