

Surge Protection Devices



15A 125V
NEMA 5-15R
UL CSA
0.5 HP




20A 125V
NEMA 5-20R
UL CSA
1 HP


Hospital Grade • Circuit Guard® Receptacles

| Description | Color | Catalog Number | |
|--|--------------|--------------------|--------------------|
| SNAPConnect® Tamper-Resistant, surge suppression duplex receptacle, smooth face, 240 joules, 15000A peak current. Requires Snap connector on page L-14, sold separately. | Blue | SNAP8262S | SNAP8362S |
| | Gray | SNAP8262GYS | SNAP8362GYS |
| | Ivory | SNAP8262IS | SNAP8362IS |
| | Light Almond | SNAP8262LAS | SNAP8362LAS |
| | Red | SNAP8262RS | SNAP8362RS |
| | White | SNAP8262WS | SNAP8362WS |
| Surge suppression receptacles with light and alarm, 240 joules, 15000A peak current. | Blue | HBL8262SA | HBL8362SA |
| | Gray | HBL8262GYSA | HBL8362GYSA |
| | Ivory | HBL8262ISA | HBL8362ISA |
| | Red | HBL8262RSA | HBL8362RSA |
| | White | HBL8262WSA | HBL8362WSA |
| Isolated ground, surge suppression receptacles with light and alarm, 240 joules, 15000A peak current. | Blue | IG8262SA | IG8362SA |
| | Gray | IG8262GYSA | IG8362GYSA |
| | Ivory | IG8262ISA | IG8362ISA |
| | Orange | IG8262OSA | IG8362OSA |
| | Red | IG8262RSA | IG8362RSA |
| | White | IG8262WSA | IG8362WSA |
| 4-PLEX® surge suppression receptacles with lights, 80 joules, 6500A peak current. | Blue | — | HBL420HS |
| | Ivory | — | HBL420HIS |
| | Red | — | HBL420HRS |


Note: See page Tech-10 for Tamper-Resistant and LED Power Indicators descriptions.



SNAP8362GYS



HBL8362ISA



HBL420HS

4-PLEX® Accessories

| Description | Color | Catalog Number |
|---|-------|-----------------|
| 4-PLEX Adapter Plates for 1- and 2-gang, and 4 in. (101.6) square device boxes. | Blue | HBL4APBL |
| | Ivory | HBL4API |
| | Red | HBL4APR |
| 4-PLEX Portable Box, 4 in. (101.6) square box with cord grip. Accepts up to .66 in. (16.8) diameter cord. | Ivory | HBL4PBI |

Note: 4-PLEX Box is not UL Listed.

UL2930 Listed



UL2930 Health Care Outlet Assembly (HCOA)

| Description | # of Outlets | Cord Length | Color | 15 Amp | 20 Amp |
|--|--------------|-------------|-------|--------------------|----------------------|
| UL 2930 HCOA with L-N surge protection. | 6 | 6' | White | HBL6MG6 | HBL6MG620 |
| | 6 | 15' | White | HBL6MG15 | HBL6MG1520 |
| UL 2930 HCOA, Relocatable Power Tap (RPT). | 6 | 6' | White | HBL6MGRPT6 | HBL6MGRPT620 |
| | 6 | 15' | White | HBL6MGRPT15 | HBL6MGRPT1520 |



HBL6MGRPT620

Listed to UL1449



SpikeShield® Surge Protective Devices (SPD) with Tamper-Resistant Receptacles and Heavy Duty Plug

| Description | # of Outlets | Cord Length | Color | 15 Amp | 20 Amp |
|--|--------------|-------------|-------|-------------------|-------------------|
| Type 3 SPD, Heavy Duty metal housing. | 6 | 6' | White | HBL6HG6 | HBL6HG620 |
| | 6 | 15' | White | HBL6HG15 | HBL6HG1520 |
| UL Type 3 SPD, Heavy Duty metal housing with 2-port USB. | 4 | 6' | White | HBL6HGUSB6 | — |



HBL6HGUSB6

Dimensions in Inches (mm)