







## 4 in. Octagonal Boxes

### Nonmetallic Sheathed Cable Clamps

		
<b>BC54151-L</b>	<b>BC54151-LB</b>	<b>BC54151-LD</b>
Prepositioned depth tabs recessed 1/2 in.	Side bracket, with holding prongs and prepositioned depth tabs.	Swing-arm" rework brackets. Max. wall thickness: 3/4 in.. Max. load capacity: 12 lb. (5.5 kg).
		
<b>BC54171-L</b>	<b>BC54171-LB</b>	<b>CI54171-LF</b>
	Side bracket, with holding prongs.	Ceiling fan box. (Supplied with 2 #10-32 machine screws and star washers.) Max. load capacity: 35 lb. (15.6 kg).




Cat. No.	Volume (Cu. in.)	Features		Knockouts		Pryouts	
		Bracket	Raised Ground Screw	1/2 in. sides	1/2 in. bottom	sides	bottom
1-1/2 in. Deep							
BC54151-L	15.0	-	yes	2	1	4	4
BC54151-LB	15.0	“B”	yes	1	1	4	4
BC54151-LD	15.0	rework	yes	-	1	4	4
CI54151-LF	15.0	-	yes	2	1	4	4
2-1/8 in. Deep							
BC54171-L	21.0	-	yes	2	1	4	4
BC54171-LB	21.0	“B”	yes	1	1	4	4
BC54171-LD	21.0	rework	-	-	1	4	4
CI54171-LF	21.0	-	yes	2	1	4	4

FOR USE WITH NONMETALLIC SHEATHED CABLE ONLY



Note: CEC 2012 rule 30-302: Subrule (4) requires that a ceiling-mounted luminaire weighing 23 kg or less be supported on a ceiling outlet box attached directly to the building structure. A bar hanger may also be used to attach a ceiling outlet box to the building structure when the luminaire weighs 23 kg or less.

## 4 in. Octagonal Boxes

### Armoured and Nonmetallic Sheathed Cable Clamps


**BC54151-LA**

**BC54151-LSSAX**

"Wraparound" bracket for 2-1/2 in. and 3-5/8 in. steel studs.  
With integral support bracket.


**BC54171-LA**

**BC54171-LSSAX**

**BC54171-LSSAX-5/8**

Brackets for use with 5/8 in. drywall.



Cat. No.	Volume (Cu. in.)	Features		Knockouts		Pryouts	
		Bracket	Raised Ground Screw	1/2 in. sides	1/2 in. bottom	sides	bottom
1-1/2 in. Deep							
BC54151-LA	15.0	-	yes	2	1	4	-
BC54151-LSSAX	15.0	“SSX”	yes	-	1	4	-
2-1/8 in. Deep							
BC54171-LA	21.0	-	yes	2	1	4	-
BC54171-LSSAX	21.0	“SSX”	yes	-	1	4	-
BC54171-LSSAX-5/8	21.0	“SSX”	yes	-	1	4	-

## 4 in. Octagonal Boxes

### Covers

			
BC54-C-1	BC54-C-6	CI54-C-64	BC54-C-65

		
BC54-C-94	BC54-COV	BC54-COV-1



Cat. No.	Description
<b>4 in. Round Covers</b>	
<b>BC54-C-1</b>	Flat blank
<b>BC54-C-6</b>	Flat with 1/2 in. conduit knockout
<b>CI54-C-64</b>	Flat for 1-13/32 in. diameter. 15 A single receptacle. Device mounting screws included
<b>BC54-C-65</b>	Flat for duplex receptacle. Device mounting screw included
<b>BC54-C-94</b>	Flat for toggle switch. Device mounting screws included
<b>5 in. Round Covers (White Enamel Paint)</b>	
<b>BC54-COV</b>	Flat with 1/2 in. conduit knockout. Mounting screws included
<b>BC54-COV-1</b>	Flat blank. Mounting screws included