

Temporary Anchorage Connectors



Cross-Arm Anchorage Connectors

6-ft. (1.8 m) web Cross-Arm Strap wraps around I-beams and other structures and attaches with a 2-in. (51 mm) D-ring that slips through a 3-in. (76 mm) D-ring to form a secure attachment point for lanyards and other connecting devices. 400-lbs. (181 kg) maximum capacity.

8183/3FTGN - 3-ft. (0.9 m) model
8183/6FTGN - 6-ft. (1.8 m) model



Looped Cross-Arm Anchorage Connectors

The looped cross-arm anchorage connector features a 2-in. (50 mm) D-ring which slips through looped webbing. 400-lbs. (181 kg) maximum capacity.

8185/3FTGN - 3-ft. (0.9 m) model
8185/6FTGN - 6-ft. (1.8 m) model
8185K/6FTBK - 6-ft. (1.8 m) Nomex/Kevlar model



Cable Anchorage Connector

The Cable Anchorage Connector creates quick, easy and secure anchorage attachment. Constructed of 1/4-in. (6 mm) vinyl-coated, galvanized cable and a steel 3-in. (76 mm) O-ring. Standard length is 6 ft. (1.8 m); additional lengths available. 400-lbs. (181.4 kg) maximum capacity.

8187V/6FTV - 6-ft. cable with steel captive eye carabiner with 1-in. (25 mm) gate opening
8186V-Z7/6FTV - 6-ft. cable with steel locking snap hook with 3/4" gate opening



Cross-Arm Chain Anchor

The 6-ft. (1.8 m) Chain Anchor provides a single user with an easy-to-install, temporary anchorage connector. It easily wraps around I-beams or other structures. This product safely wraps around corners and sharp edges and is ideal to use in environments where chemical, heat or welding splatter may occur. 400-lbs. (181 kg) maximum capacity.

440/6FT



Disposable Concrete Anchor Strap

Uniquely designed to provide temporary anchorage on concrete forms. Constructed of 1-3/4-in. (44 mm) wide, abrasion-resistant webbing. Standard lengths of 2 ft. (.6 m) and 4 ft. (1.2 m); additional lengths available.

8185C/4FTGN - anchor strap with steel D-ring capable of withstanding 5,000 lbs. (22 kN).

8185CX/4FTGN - anchor strap with web loop on each end with inner wear pad for carabiner attachment



Rebar Hook Anchor

Designed to facilitate anchoring to scaffolding, pipe or angle iron, and features a locking rebar hook with SofStop Shock Absorber and a D-ring on the other end to accommodate the connecting device. 310-lbs. (140.6 kg) maximum capacity.

485-Z7/22INYLK

Features a locking rebar hook for easy, one-hand installation and a D-ring on the other end to accommodate the connecting device. 400-lbs. (181.4 kg) maximum capacity.

480-Z7/19INGN



Push-Thru Eye Bolt Anchors

Spring-action anchorage connector offers simple one-hand installation and can be used for a wide range of applications. Fits 3/4-in. (19 mm) dia. holes and includes the integral SofStop Shock Absorber.

420/22IN; 310-lbs. (140.6 kg) maximum capacity.
420NS/ (w/o shock absorber); 400-lbs. (181 kg)



Wire Hook Anchor

Stainless steel Wire Hook connects to various approved anchorages including railings, small I-beams, angle iron and scaffolding. Simply squeeze the spring-loaded hook and slip the large opening over the approved structure. 400-lbs. (181 kg) maximum capacity.

470/



Aerial Lift Boom Strap

Made of 2-in. (51 mm) nylon webbing. Includes a sliding D-ring for proper placement on booms and an adjustable buckle that easily tightens into position.
6404/50INYL



Boom Strap

Made of 2-in. (51 mm) polyester webbing. Features a steel ratchet buckle with a leather wear pad.
M10FD/10FTYL



Extension Pole and Hook Anchors

The 20-ft. (6 m) fiberglass pole and spring-loaded hook is ideal for use with climbing ladders and towers. Installs fall arrest systems up to 20 ft. (6 m) from ground level to angle iron, piping and related structures. 400-lbs. (181 kg) maximum capacity.
475/
475-1/ (Anchor Hook only)
475-2/ (Anchor Extension Pole only)



Beam Clamps

The Beam Clamp is a steel anchor point that can be attached to horizontal I-beams, S-beams or W-beams. Its swivel attachment ring prevents twisting of the worker's connecting device.
450/ accommodates beams with a maximum width of 9 in. (229 mm).
455/ accommodates beams with a maximum width of 12-1/2 in. (318 mm), 400-lbs. (181.4 kg) maximum capacity.



Concrete D-Bolt Anchorage Connector

417C/ includes a 5/8-in. (16 mm) stud-type expansion anchor that is ideal for applications with concrete and lightweight concrete that meet required specifications (min. 2,000 psi [13.8 MPa]). Can be installed on a vertical wall or overhead for versatility. Concrete Expansion Bolt (417CBOLT/) available separately.
417C/ - Concrete D-Bolt Anchorage Connector
417CBOLT/ - Concrete Expansion Bolt



Carabiners – 400-lbs. (181.4 kg) maximum capacity
Steel double-lock carabiner;
1-in. (25 mm) gate opening.
17D-1/



Lightweight, aluminum double-lock carabiner;
.79-in. (20 mm) gate opening.
17D-2-Z7/



Lightweight, aluminum triple-lock carabiner;
.94-in. (24 mm) gate opening.
17D-3-Z7/



Large, steel double-lock carabiner;
2-in. (51 mm) gate opening.
18D-1/



Large, aluminum double-lock carabiner;
2-in (51mm) gate opening.
18D-2-Z7/