GALAXY GX2 System Ordering Information

GALAXY GX2 System Test Stand				
	1 Valve (for use with 1 calibration gas cylinder)		4 Valve (for use with 1-4 calibration gas cylinders)	
	Charging*	No-charging	Charging*	No-charging
ALTAIR / ALTAIR PRO Single-Gas Detector	–	10128644	–	10128643
ALTAIR 4/4X Multigas Detector	10128630	10128642	10128629	10128641
ALTAIR 5/5X Multigas Detector	10128626	10128628	10128625	10128627

** Contact your local sales representative regarding availability.*

The GALAXY GX2 System test stand comes with pre-configured plugs, barbs, fresh air filter, power supply with corresponding plug, spare parts kit (gas tubing, barbs and plugs), Ethernet cable (short cable for connection between test stands), and screen protector. Please see ordering information below for further system components, including electronic cylinder holder (includes regulator) or non-electronic cylinder holder (without regulator), MSA Link Pro Software, digital secure USB key, end cap, and multi-unit charger.

Accessories

P/N	Description
10105756	Electronic cylinder holder
10125135	Non-electronic cylinder holder
10127111	4 GB SD card
10123938	MSA Link Pro Software key
10123937	Digital secure USB key
10125907	End cap
10127422	ALTAIR 4/4X Detector Multi-unit Charger, NA
10127427	ALTAIR 5/5X Detector Multi-unit Charger, NA
10127808	Sticker or receipt / sticker printer
10127807	Printer cable
10126437	Detector sticker label roll
10126438	Receipt & sticker label roll
10127112	Laminated quick start guide
10127518	12" (TBR) Ethernet cable for test stand to test stand connection
10126657	DIN rail clip kit (2 clips & screws per kit)
10062364	Type Omega DIN Rail 0.5m, perforated, steel, zinc-plated
10062365	Type Omega DIN Rail 1m, perforated, steel, zinc-plated
10062366	Type Omega DIN Rail 2m, perforated, steel, zinc-plated
10082834	USB IR dongle (for use with MSA Link Software)
10034391	Demand flow regulator (universal)
710289	Large capacity (<3000 psi) demand regulator
10126268	Vehicle power adapter

Calibration Gas

P/N	Description
10048280	Calibration gas cylinder (34L) 1.45% CH_4, 15% O_2, 60 ppm CO, 20 ppm H_2S
10045035	Calibration gas cylinder (54L) 1.45% CH_4, 15% O_2, 60 ppm CO, 20 ppm H_2S
10117738	Calibration gas cylinder (58L) 1.45% CH_4, 15% O_2, 60 ppm CO, 20 ppm H_2S, 10 ppm SO_2
10098855	Calibration gas cylinder (34L) 1.45% CH_4, 15% O_2, 60 ppm CO, 20 ppm H_2S, 10 ppm SO_2
10103262	Calibration gas cylinder (58L) 1.45% CH_4, 15% O_2, 60 ppm CO, 20 ppm H_2S, 2.5% CO_2

Technical Specifications

Operating Temperature	GALAXY GX2 System	0-40˚C
Power Input	Power module	100-240 VAC, 47-63 Hz
	Optional vehicle module	9-32 VDC
Physical Characteristics	Test stand	Height: 11.80" (299.72 mm)
		Width: 6.50" (165.10 mm)
		Depth: 7.90" (200.66 mm)
		Material: acrylonitrile butadiene ABS
	Cylinder holder	Height: 11.80" (299.72 mm)
		Width: 6.50" (165.10 mm)
		Depth: 6.10" (154.94 mm)
		Material: acrylonitrile butadiene ABS
	Multi-unit charger	Height: 11.80" (299.72 mm)
		Width: 6.50" (165.10 mm)
		Depth: 6.44" (163.58 mm)
		Material: acrylonitrile butadiene ABS

Note: This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.

ID 0818-18-MC / Aug 2012
© MSA 2012 Printed in U.S.A.

MSA Corporate Center
1000 Cranberry Woods Drive
Cranberry Township, PA 16066 USA
Phone 724-776-8600
www.MSAsafety.com

U.S. Customer Service Center
Phone 1-800-MSA-2222
Fax 1-800-967-0398

MSA Canada
Phone 1-800-672-2222
Fax 1-800-967-0398

MSA Mexico
Phone 01-800-672-7222
Fax 52-44 2227 3943

MSA International
Phone 724-776-8626
Toll Free 1-800-672-7777
FAX 724-741-1559

MSA Europe
Phone +49 (0) 306886-0
Fax +49 (0) 306886-1558

MSA
The Safety Company